

## TERRALUX TLE-HP3

### *SPECIFICATIONS*

- 180 Lumens at maximum light output.
- Replaces halogen bulb with long life LED.
- Runtime approximately 6 hours.
- This upgrade is designed for 3.6 VDC input voltage of the Streamlight HP flashlight. Usage in other products/voltages may damage units and void warranty.

### *INSTALLATION INSTRUCTIONS*

To install the Terralux TLE-HP3 into a Streamlight HP®

6. First unscrew the head of the flashlight, and remove the original bulb inside and the spring. Leave the O-ring in place.
7. Align the TLE-HP3 so that the rectangular notch on the outer edge of the heat sink is pointing toward the exposed screw on the inside of the flashlight.
8. Carefully install the TLE-HP3 so that the bottom pins engage into the battery connector of the flashlight without twisting.
9. Test the installation by turning on the flashlight. If there is no light output, check your orientation(s) and gently push down on the TLE-HP3 to insure the battery contact is being made.
10. Re-install the spring around the outer plastic housing of the TLE-HP3 and re-install the head. Your flashlight is now ready to use.

\*Disclaimer: Terralux is not affiliated with Streamlight, Inc. which owns the STREAMLIGHT® trademark and the STINGER® line of trademarks. Streamlight Inc.'s trademarks are used here only to identify the flashlights with which TerraLUX intends its products to work. TerraLUX's products are not made, endorsed, or sponsored by Streamlight, Inc.