

TERRALUX TLE-US MM

SPECIFICATIONS

- 300 Lumens at maximum light output.
- Replaces halogen bulb with long life LED.
- Electronic regulation for constant light output.
- 3 Dimming Levels.
- Over-temperature protection.
- Runtime 2 hours at full power, 6 hours at medium and over 24 hours on low.

INSTALLATION INSTRUCTIONS

To install the Terralux TLE-US MM into a Streamlight Ultra Stinger®

1. First unscrew the head of the flashlight, and remove the original bulb inside and the spring. Leave the O-ring in place.
2. Align the TLE-US MM so that the half circular notch on the outer edge of the heat sink is pointing toward the exposed screw on the inside of the flashlight.
3. Carefully install the TLE-US MM so that the bottom pins engage into the battery connector of the flashlight without twisting.
4. Test the installation by turning on the flashlight. If there is no light output, check your orientation(s) and gently push down on the TLE-US MM to insure the battery contact is being made.
5. Re-install the spring around the outer plastic housing of the TLE-US MM and re-install the head.

Your flashlight is now ready to use.

***Disclaimer: Terralux is not affiliated with Streamlight, Inc. which owns the STREAMLIGHT® trademark and the STINGER® line of trademarks. Streamlight Inc.'s trademarks are used here only to identify the flashlights with which TerraLUX intends its products to work. TerraLUX's products are not made, endorsed, or sponsored by Streamlight, Inc.**